

# Model: BPC1500-C2D

15" LCD, Core 2 Duo Mobile Processor  
Rugged Multi-Slot Portable Battery Computer



## FEATURES:

- All-in-one design rugged portable computer
- Compact Size Lightweight Design
- Built-in 15" LCD display with tempered glass
- 250W PSU or 190W Li-ion battery packs, up to 4 hours battery life
- Mini-ITX MB, Intel Core 2 Duo T7500 Processors
- Keyboard multi-language with touchpad
- 3x PCI-E (x8) full-length expansion slots, Option 3x PCI-X or 2x PCI, 1x PCI-E (x16)
- Built-in 320GB, Support 2x 2.5" removable HDD
- Dual Gigabit Ethernet, 2x COM Port
- Carrying case to manage portable PC with ease

## Options:

- Intel T9400 (2.53GHz )
- Touch Screen
- Sunlight Readable
- 2x 2G RAM
- Air Cargo



Carrying Case



Air Cargo Case



i-Tech Company LLC  
TOLL FREE: (888) 483-2418 • EMAIL: [info@itechlcd.com](mailto:info@itechlcd.com) • WEB: [www.iTechLCD.com](http://www.iTechLCD.com)

Specifications	
<b>Construction</b>	Rugged Aluminum Construction with rubber corners
<b>CPU</b>	Intel Core 2 DuoT7500 (2.2GHz) Processors
<b>Chipset</b>	Intel Gm45 Chipset + ICH9M
<b>Slot</b>	3x PCI-E (x8) full-size slots Option: 3x PCI-X full-size slots Option: 2x PCI, 1x PCI-E (x16) full-size slots
<b>Display</b>	15" LCD display, 1024x 768, 16.2M, MTBF: 50,000 hrs. 250 nits, Anti-reflection tempered strengthen glass
<b>Memory</b>	2GB RAM (Up to 4GB Max)
<b>HDD</b>	1x 320GB 2.5", 7200 rpm SATA HDD Support 2x 2.5" Hot-Swappable SATA
<b>CDROM</b>	1x Slim DVD-RW
<b>Interfaces</b>	4x USB 2.0 Ports, 1x VGA Port, 2x Gigabit LAN, 2x COM port, PS2 KB/MS, Audio
<b>Audio</b>	ICH9M built-in audio HD audio w/ Realtek ALC888
<b>LAN</b>	Dual Gigabit LAN, RJ-45 connector
<b>KB/MS</b>	Notebook type keyboard with touchpad
<b>PSU/Battery</b>	250W, 100~240 VAC, Auto switch
<b>Dimension</b>	412x 305x 184 mm (Wx Hx D)
<b>Weight</b>	9 kgs
<b>Carrying Case</b>	Padded carrying case with wheels

Environmental Factors		
	Operating	Non-Operating
<b>Temperature</b>	0°C~50°C	-20°C~60°C
<b>Relative Humidity</b>	10%~90%	10%~95%
<b>Shock</b>	10g, 11ms, half-Sine	30g, 11ms, half-Sine
<b>Vibration</b>	10-500Hz (0.4 Grms)	10-500Hz (1.12 Grms)
<b>Approval</b>	CE, FCC, RoHS	

