

1U Rackmount 17" TFT LCD Monitor Dual Slides Optional 8-port/16-port KVM switch



Specification

Model No	BHK1017e / 1017-8e / 1017-16e
Ports switch	D-Sub 15 pin
Weight	16kgs
Dimension	442.4 x 44.5 x 550mm (WxHxD)
Power Supply	AC 110/220V Auto Switch or DC+48V
Construction	Heavy-duty steel
Keyboard	Membrane 105 keys with touchpad
Protection	Tempered glass protection to the LCD screen
Operation Temp.	0-50°C(32-122°F)
Approval	CE, FCC
Display	
Diagonal	17" (431.8mm)
LCD Resolution	1280 x 1024
Brightness	300 nits
Viewing angle	160/160
Contrast Ratio	450:1
Backlight MTBF	50,000 hours under 20 - 30°C
Frame Rate	60Hz

Accessories	Extension Bracket	Power cord	Adjustable bracket Max. Length	KVM Cable
BHK1017e	X 1 pair	x 1	22.5"-35.5"	x 1
BHK1017-8e	X 1 pair	x 1	25"-37"	x 8
BHK1017-16e	X 1 pair	x 1	24.5"-37.5"	x 16

Order Information

Weight (Net / Gross weight)	
BHK1017e	33.0 lbs / 44.0lbs (15 kg/20 kg)
BHK1017-8e	35.2 lbs / 46.2 lbs (16 kg/21 kg)
BHK1017-16e	37.4 lbs / 48.2 lbs (17 kg/22 kg)
Dimensions	
BHK1017e	442.4(17.4")W x 44.5 (1.75")H x 480(18.9")D
BHK1017-8e	442.4(17.4")W x 44.5 (1.75")H x 590(23.2")D
BHK1017-16e	442.4(17.4")W x 44.5 (1.75")H x 590(23.2")D

Model: BHK1017e, BHK1017-8e, and BHK1017-16e

Features:

- Only 1U (1.75" high) of vertical 19" rack-mount space.
- Meets EIA310c & IEC-3 Specifications
- Full 101-keys Windows keyboard
- Support DOS, Windows OS, Netware, SCO Unix, HP Unix, Linux
- Anti-Glare Tempered Glass for added protection
- Auto LCD turned off when LCD screen is turned down position.
- Built-in Rail Self-locking device
- Standard keyboard, mouse and VGA Cable
- Built-in power adapter
- Keyboard with GlidePoint touch pad mouse
- Built-in on screen display controlled by integral membrane switches

With KVM Option only:

- **Multi-platform-mix** PCs, SUNs, IBMs, HPs, Compaq & DELL
- **Support 8 characters password protection** & search PC server name
- **Cascades for use with up to 128 servers**
- New keep alive feature safeguards server for power loss to the switch
- **Built-in microprocessor** emulation for each port boots up process
- **Auto scan-mode** for monitoring your servers at intervals 5 to 99s
- **Hot-plug** when adding or removing PC w/o powering down the switch
- Name your server up to **16 characters long**

BHK1017e



BHK1017-8e



BHK1017-16e

